



1 Heizpatronen Cartridge Heaters



Inquiry form

Specifications:

Diametre round cartridge heater: mm unipolar (standard 24V)
 Cross section square cartridge heater: mm
 Total length: mm Voltage: V
 Quantity: pieces Wattage: W

Options:

Thermocouple (p. 8)

Thermosensor type J (Fe-CuNi, red / blue) Thermosensor type K (NiCr-Ni, red / green)

Connection Type (p. 8)

Type I internally connected (standard for $\varnothing \leq 8\text{mm}$)
 Type N externally connected (standard for $\varnothing > 8\text{mm}$)
 Type F contacted in ceramic cap

Leads Type (p. 9)

Fibre glass insulated leads (standard 250mm) 300°C PTFE insulated leads (no standard) 260°C
 Silicone insulated leads (no standard) 180°C High temperature leads (no standard) 500°C

Leads length: mm

Earth lead: Yes No

Protection Sleeve (p. 13)

Silicon impregnated fibreglass sleeve Braided metal sleeve
 Stainless steel sleeve Flexible metal conduit
 Silicone cable

Length: mm

Termination Type (p. 10-12)

Type A Type B Type C Type D

Miscellaneous

Sender address:

Company: Name:
 Street: Telephone:
 Zip / Town: / E-Mail:

Telephone: +49 - (0)23 73 - 95 90-0
 Telefax: +49 - (0)23 73 - 95 90-30

